

# **SAFETY DATA SHEET**

Issue Date 03-MAY-2021 Revision Date 06-NOV-2023 Version 1

#### 1. IDENTIFICATION

**Product identifier** 

Product Name CUTBACK ASPHALT FOR DUCTILE AND CAST IRON

Other means of identification

Product Code Tuffcoat OD

**SKU #** 727

Recommended use of the chemical and restrictions on use

Recommended Use Pipe Coating

Uses advised against No information available

# Details of the supplier of the safety data sheet

**Manufacturer Address** 

ROYAL COATINGS. INC

3014 Dauphine St Ste A, PMB 48447,

New Orleans, LA 70117-6755

Company Contact: Technical Services Telephone Number: 504-392-8811 Web Site: www.royalcoatings.net sales@royalcoatings.net

**Emergency telephone number** 

Emergency telephone CHEMTREC: 800-424-9300

CHEMTREC: 703-527-3887

# 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Not classified
Acute toxicity - Dermal	Not classified
Acute toxicity - Inhalation (Gases)	Not classified
Acute toxicity - Inhalation (Vapors)	Not classified
Acute toxicity - Inhalation (Dusts/Mists)	Not classified
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Respiratory sensitization	Not classified
Skin sensitization	Not classified
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Not classified
Specific target organ toxicity (single exposure)	Not classified
Specific target organ toxicity (repeated exposure)	Not classified
Aspiration toxicity	Not classified
Flammable liquids	Category 3

#### Label elements

#### **Emergency Overview**

#### Warning

#### Hazard statements

Causes skin irritation

Causes serious eve irritation

May cause respiratory irritation. May cause drowsiness or dizziness

Flammable liquid and vapor



Appearance paste

Physical state liquid Odor Petroleum distillates

#### **Precautionary Statements - Prevention**

Wear protective gloves/protective clothing/eye protection/face protection Keep away from heat/sparks/open flames/hot surfaces. - No smoking Wash face, hands and any exposed skin thoroughly after handling

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention IF ON SKIN: Wash with plenty of soap and water

If skin irritation occurs: Get medical advice/attention

IF INHALED: Call a POISON CENTER or doctor if you feel unwell In case of fire: Use Water spray, fog or regular foam for extinction

# Hazards not otherwise classified (HNOC)

Not applicable

### Other Information

Harmful to aquatic life with long lasting effects

Unknown acute toxicity 29.97% of the mixture consists of ingredient(s) of unknown toxicity

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Substance

Chemical Name	CAS No.	Weight-%	Trade Secret
Petroleum Asphalt	8052-42-4	50-70	*
Stoddard solvent	8052-41-3	20-30	*
Aromatic Solvent	64742-95-6	5-15	*
1,2,4 Trimethylbenzene	95-63-6	1-5	*

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

# 4. FIRST AID MEASURES

# **Description of first aid measures**

**Eye contact**Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids.

#### Tuffcoat OD - CUTBACK ASPHALT FOR DUCTILE AND CAST IRON

Consult a physician.

**Skin contact** Wash skin with soap and water.

**Inhalation** Remove to fresh air.

**Ingestion** Clean mouth with water and drink afterwards plenty of water.

Most important symptoms and effects, both acute and delayed

Symptoms Drowsiness.

Indication of any immediate medical attention and special treatment needed

**Note to physicians**Treat symptomatically.

# 5. FIRE-FIGHTING MEASURES

#### Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media CAUTION: Use of water spray when fighting fire may be inefficient.

### Specific hazards arising from the chemical

No information available.

#### Explosion data

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

#### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

# **6. ACCIDENTAL RELEASE MEASURES**

#### Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas.

**Environmental precautions** 

**Environmental precautions** See Section 12 for additional ecological information.

#### Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up** Pick up and transfer to properly labeled containers.

#### 7. HANDLING AND STORAGE

#### Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice.

# Conditions for safe storage, including any incompatibilities

Petroleum distillates

No information available

Storage Conditions Keep containers tightly closed in a cool, well-ventilated place. Keep away from heat,

sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static

electricity).

**Incompatible materials** Strong oxidizing agents.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

**Exposure Guidelines**This product, as supplied, does not contain any hazardous materials with occupational

exposure limits established by the region specific regulatory bodies.

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Petroleum Asphalt 8052-42-4	TWA: 0.5 mg/m <sup>3</sup> benzene soluble aerosol fume, inhalable fraction	-	Ceiling: 5 mg/m <sup>3</sup> fume 15 min
Stoddard solvent 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m³ (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m³	IDLH: 20000 mg/m³ Ceiling: 1800 mg/m³ 15 min TWA: 350 mg/m³
1,2,4 Trimethylbenzene 95-63-6	-	-	TWA: 25 ppm TWA: 125 mg/m <sup>3</sup>

### **Appropriate engineering controls**

Engineering Controls Showers

Eyewash stations Ventilation systems.

# Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin and body protection** Wear protective gloves and protective clothing.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

Odor

**Odor threshold** 

provided in accordance with current local regulations.

**General Hygiene Considerations** Handle in accordance with good industrial hygiene and safety practice.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Information on basic physical and chemical properties

Physical stateliquidAppearancepasteColorblack

Property Values Remarks • Method

pH No information available

Melting point / freezing point No information available

**Boiling point / boiling range** >= 150 °C **Flash point** 40 °C

Flash point 40 °C
Evaporation rate No information available
Flammability (solid, gas) No information available

Flammability Limit in Air

Upper flammability limit: 9%
Lower flammability limit: 1%

Vapor pressure No information available

#### Tuffcoat OD - CUTBACK ASPHALT FOR DUCTILE AND CAST IRON

\_\_\_\_\_

@ 40 °C

Vapor density No information available

Relative density 0.9 - 1.3

Water solubility
Solubility in other solvents
Partition coefficient
Autoignition temperature
Decomposition temperature
No information available
No information available
No information available
No information available

Kinematic viscosity >100 mm2/s

Dynamic viscosityNo information availableExplosive propertiesNo information availableOxidizing propertiesNo information available

**Other Information** 

Softening point
Molecular weight
VOC Content (%)
Density
No information available

# 10. STABILITY AND REACTIVITY

#### Reactivity

No data available

#### **Chemical stability**

Stable under recommended storage conditions.

# Possibility of Hazardous Reactions

None under normal processing.

# **Conditions to avoid**

Extremes of temperature and direct sunlight.

# **Incompatible materials**

Strong oxidizing agents.

# **Hazardous Decomposition Products**

None known based on information supplied.

# 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Product Information No data available

**Inhalation** May cause irritation of respiratory tract. May cause drowsiness or dizziness.

**Eye contact** Irritating to eyes.

**Skin contact** Irritating to skin.

**Ingestion** No data available.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Petroleum Asphalt	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	-
8052-42-4			
1,2,4 Trimethylbenzene	= 3280 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 18 g/m <sup>3</sup> (Rat) 4 h
95-63-6			

#### Information on toxicological effects

**Symptoms** Vapors may cause drowsiness and dizziness.

Revision Date 06-NOV-2023

#### Tuffcoat OD - CUTBACK ASPHALT FOR DUCTILE AND CAST IRON

Tuilcoat Ob OT BACK ACITIAL TOK BOOTILL AND GACT INCH

# Delayed and immediate effects as well as chronic effects from short and long-term exposure

SensitizationNo information available.Germ cell mutagenicityNo information available.

Carcinogenicity

Chemical Name	ACGIH	IARC	NTP	OSHA
Petroleum Asphalt	-	Group 2B	-	X
8052-42-4		-		

Reproductive toxicity
STOT - single exposure
STOT - repeated exposure
Aspiration hazard
No information available.
No information available.
No information available.

#### Numerical measures of toxicity - Product Information

 ATEmix (oral)
 5,602.00

 ATEmix (dermal)
 5,602.00

 ATEmix (inhalation-gas)
 99,999.00

 ATEmix (inhalation-dust/mist)
 14.01

 ATEmix (inhalation-vapor)
 99,999.00

# 12. ECOLOGICAL INFORMATION

# **Ecotoxicity**

49.4 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

### Persistence and degradability

Not readily biodegradable.

# **Bioaccumulation**

No information available.

Chemical Name	Partition coefficient
Petroleum Asphalt 8052-42-4	>6
1,2,4 Trimethylbenzene	3.63

Other adverse effects No information available

Ozone Not applicable

# 13. DISPOSAL CONSIDERATIONS

# Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

# 14. TRANSPORT INFORMATION

**DOT**Not regulated (If shipped in NON BULK packaging by ground transport)

TDG Not regulated

<u>IATA</u>

UN1999
Proper shipping name UN1999
Tars, Liquid

Hazard Class 3
Packing Group III

**IMDG** 

UN/ID no. UN1999
Proper shipping name Tars, Liquid

Hazard Class 3
Packing Group III

**Description** May be transported as non-hazardous in accordance with IMDG 2.3.2.5

#### 15. REGULATORY INFORMATION

All components used in this product are on the TSCA Inventory and the Canadian DSL.

# International Inventories

**TSCA** Complies Complies **DSL/NDSL** Complies **EINECS/ELINCS** Does not comply **ENCS IECSC** Complies **KECL** Complies **PICCS** Complies Complies **AICS** 

#### <u>Legend:</u>

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

# US Federal Regulations

### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

# SARA 311/312 Hazard Categories

Acute health hazard Yes
Chronic Health Hazard No
Fire hazard No
Sudden release of pressure hazard No
Reactive Hazard No

# **CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

#### **CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

### **US State Regulations**

#### **California Proposition 65**

This product contains chemicals known to the state of California to cause cancer

# U.S. State Right-to-Know Regulations

### U.S. EPA Label Information

**EPA Pesticide Registration Number** Not applicable

# 16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 2 Flammability 2 Instability 0 Physical and Chemical

Properties -

HMIS Health hazards 2 Flammability 2 Physical hazards 0 Personal protection X

 Issue Date
 03-MAY-2021

 Revision Date
 03-MAY-2021

**Revision Note** 

No information available

#### **Disclaimer**

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**